

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 August 2003 (21.08.2003)

PCT

(10) International Publication Number
WO 03/068304 A1

(51) International Patent Classification⁷: A61M 25/02

(21) International Application Number: PCT/GB03/00539

(22) International Filing Date: 12 February 2003 (12.02.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0203713.3 16 February 2002 (16.02.2002) GB

(71) Applicant and

(72) Inventor: MOGG, Alan, David [GB/GB]; 3 Farm Road,
West Moors, Ferndown, Dorset BH22 0JA (GB).

(74) Agent: BARKER BRETTEL; Medina Chambers, Town
Quay, Southampton SO14 2AQ (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CATHETER CLAMP



(57) Abstract: A catheter clamp (1) comprising a body portion (5) and clamping means (3), the body portion comprising a first location portion (11) which receives a catheter (2) which issues from a patient's skin, a second location portion (12) which causes the catheter to be bent through an arc and third location portion (13) which guides the catheter to an exit of the clamp, the third location portion comprising side walls which flank the catheter so as to form a close-fitting pathway, the arrangement of the clamp being such that in use the clamping means is manually operable and can be caused to adopt a clamping condition in which the clamping portion clamps at least one of that portion of the catheter which is located by the third location portion and that portion of the catheter which is located by the second location portion. The inventive catheter clamp is advantageously of a lower profile than known catheter clamps.

WO 03/068304 A1

CATHETER CLAMP

The present invention relates to catheter clamps for attaching catheters to patients' skin at an insertion site.

5 Catheters can be inserted into patients where there is a requirement, for example, to administer continuous or repeated doses of analgesia, such as epidurals, spinals or nerve blocks, or to provide intravenous feed lines, chest drains etc.

10 Catheters are typically flexible tubes of small diameter which are difficult to hold and consequently easily pulled from the patient or the end displaced, thereby causing ineffective pain control when used to administer analgesia. Also flexure of the catheter can cause analgesia to leak back along the outside of the catheter.

15 Catheter clamps are known which seek to overcome those disadvantages. Some known clamps, despite their ability to provide good clamping nevertheless have, over time, shown that there is scope for further development of catheter clamps.

The present invention seeks to provide an improved catheter clamp.

20 According to a first aspect of the invention there is provided a catheter clamp comprising a body portion and a clamping means, the body portion comprising catheter location means, the catheter location means comprising a first location portion which receives a catheter which issues from a patient's skin, a second location portion which causes the catheter to be bent through an arc and a third location portion which guides the catheter to an exit of the clamp, the third location portion comprising
25 side walls which flank the catheter so as to form a close-fitting pathway,

the arrangement of the clamp being such that in use the clamping means is manually operable and can be caused to adopt a clamping condition in which the clamping portion clamps at least one of that portion of the catheter which is located by the third location portion and that portion of
5 the catheter which is located by the second location portion.

In a preferred embodiment of the invention the fact that the clamping means is arranged to engage with that portion of the catheter which is located by a channel which guides the catheter to the exit of the device advantageously allows the device to be of a lower profile on a patient's
10 skin. Such a lower profile alleviates a clinician's perception of discomfort of the clamp when in situ.

Preferably the clamping means comprises a hinge and an arm, the hinge pivotally mounting the arm to the body portion.

Preferably the arm comprises arm retention means adapted to hold the
15 arm in a clamping condition, said arm retention means comprising co-operating formations provided on said arm and on the body portion.

Most preferably the hinge and the arm are provided substantially diametrically of the clamping portion.

The clamping means preferably comprises a clamping surface which has
20 a longitudinal cross-sectional profile which is substantially the same as that of the third location portion.

In the clamping condition the clamping means desirably at least partially encloses a region in which the insertion site is located.

Preferably, in the clamping condition respective complementary interface surfaces of the clamping means and the body bear against each other to form a barrier to the insertion site which substantially prevents an ingress of bacteria.

- 5 Advantageously since the clamping means provides such a barrier the need, with its attendant cost, for applying a dressing is obviated.

In a preferred embodiment the clamping means comprises a cap which is provided with a substantially transparent portion through which the insertion site may be viewed, whereas applying a dressing to a known
10 clamp can inhibit a clear view of the site. A further disadvantage of the application of a dressing is that such makes release of the clamp for access to the insertion site potentially problematic and cumbersome.

The clamping means preferably comprises a formation in the respective bearing surface which in part allows the catheter to exit the device. In a
15 preferred embodiment the formation results in a close-fitting arrangement.

The third location portion preferably comprises catheter gripping means which at least substantially restricts movement of the catheter in a direction which is substantially parallel to a longitudinal axis of the third
20 location portion.

The gripping means preferably comprises a rib which extends substantially perpendicular to the longitudinal axis of the third location portion. Most preferably a plurality of such ribs is provided.

The body portion preferably comprises viewing means which allows a region proximal to the insertion site to be viewed. The viewing means is preferably provided by at least one aperture.

One embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:-

Figure 1 is a cross-sectional view of a catheter clamp in a clamping condition and a catheter on A-A;

Figure 2 is a plan view of the body of the catheter clamp shown in Figure 1 in which the cap of the clamp, the catheter and the mounting pad have been omitted for clarity;

Figure 3 is a plan view of the clamp shown in Figures 1 and 2 in a closed condition in which the catheter and the mounting pad have been omitted for clarity;

Figure 4 is a cross-sectional view of the clamp in the clamping condition as shown in Figure 3 on B-B;

Figure 5 is a cross-sectional view of the clamp in the clamping condition as shown in Figure 3 on C-C;

Figure 6 is a partial cross-sectional view of the location channel on E-E;

Figure 7 is a cross-sectional view of the body of the clamp on F-F in which the mounting has been omitted for clarity;

Figure 8 is a cross-sectional view of part of the body of the clamp on D-D in which the mounting pad is omitted for clarity;

5 Figure 9 is a cross-sectional view of a clamp similar to that shown in Figure 1 in which the clamp is adapted to receive a catheter which exits the patient's skin at an angle other than 90°;

Figure 10 shows a perspective view of the catheter clamp shown in Figure 1 in a clamping condition in which the catheter is omitted for clarity;

10 Figure 11 shows a perspective view of the catheter clamp shown in Figure 1 in an open condition in which the catheter is omitted for clarity.

With reference initially to Figure 1 there is shown a catheter clamp 1 comprising a body 5 and a cap 3 of arm-like form, the cap 3 being pivotally mounted with respect to the body. The arrangement of the clamp 1 being such that in the clamping condition shown in Figure 1 the cap 3 acts upon a catheter 2 so as to clamp the catheter between the cap and the base.

20 The body 5 is adhered to a mounting pad 7 which is made of a closed-cell resilient foam material. The mounting pad 7 is provided with an aperture 10 which is substantially central of the body 5.

The body 5 comprises location means in the form of a passageway which comprises a first location portion 11, a second location portion 12 and a third location portion 13. A semi-circular vertical wall 11 defines the first location portion.

The second location portion is defined by a curved edge portion 12 whose surface extends from a substantially vertically orientation to a substantially horizontal orientation.

The third location portion 13 comprises an inclined channel 14 and a substantially horizontal channel portion 15.

The inclined channel 14 comprises three equi-spaced ribs 16 which extend substantially perpendicular to the longitudinal axis of said inclined channel.

The first location portion 11, the second location portion 12 and the inclined channel portion of the third location portion are formed in a bridge portion 24, the bridge portion 24 extending diametrically across a circular space which is defined by the radially inwardly directed surfaces 27 (as best seen in Figure 2).

As viewed in Figure 1 the bridge portion 24 comprises two flat uppermost surfaces 30, an inclined surface 31 and two inclined surfaces 32 which flank the inclined channel 15. The surfaces 27 and the bridge section 24 define two substantially D-shaped apertures which are located on each side of the bridge portion.

Adjacent and perpendicular to the radially inwardly directed surfaces 27 there is provided an upwardly facing part-annular interface surface 26, as best seen in Figure 2.

Standing proud of the interface surface 26 there are provided two tapered side walls 35 and 36 which are situated at each side of the interface surface 26 and extend along the length of the body. Each side wall each

comprises two substantially straight portions interposed by a central arcuate portion.

The horizontal channel portion 15 is provided by a recess in a tapered front wall 40 which is of arcuate outline, the recess being aligned with the inclined channel 14.

The horizontal channel portion 15 is provided by a recess formed in the interface surface 26 and is aligned with the inclined channel 14. An inclined front wall 40 is formed with a recess 41 which is aligned with the channel portion 15.

10 The front wall 40 comprises an upper surface 42 which is at a level which is above the vertical level of the interface surface 26, but below the vertical level of the side walls 35 and 36.

The body 5 further comprises a tapered rear wall 45 of arcuate outline which is located adjacent to the interface surface 26. The rear wall 45 comprises an upper surface 46 which is of substantially part-annular shape and is concentric with the interface surface 26.

Hinge grooves 50 and 51 are provided to each side of side walls 35 and 36 respectively. The hinge grooves 50 and 51 being attached to hinged portions 52 and 53 respectively.

20 Those portions (referenced 38 and 39) of the side walls 35 and 36 which are located towards the front end of the body 5 are provided on their respective inwardly facing surfaces with recesses 55 and 56 which taper downwardly. Downwardly facing flange portions 61 and 62 are provided on an underside of the portions 38 and 39. Two moulding recesses 57

and 58 are located proximal to the side wall portions 38 and 39 which extend through a base portion 70 of the body and into said wall portions.

With reference in particular to Figures 1, 3 and 4 the cap 3 comprises a central portion 84 of generally circular outline which is interposed
5 between two limbs 81 and 82, said limbs being substantially diametrical to the central portion 84.

The central portion 84 is essentially of frusto-conical shape with an uppermost surface 85 and a part-conical wall 86 around said uppermost surface.

10 The underside of the cap 3 is provided with a downwardly extending (when viewed in the condition shown in Figure 1) abutment 90 of part annular shape.

The abutment 90 comprises a lowermost interface surface 91 and has formed therein a substantially semi-circular shaped recess 92.

15 The front limb 82 comprises two spaced depending portions 112 and 113 each of which is provided with clips 59 and 60 respectively. The upper surface of the limb 82 comprises two substantially V-shaped grooves 80.

The limb 81 which is situated towards the rear of the clamp is hinged to the body by way of a pivot having rounded distal ends 95 and 96 which is
20 integral with the cap 3. Each pivot end is located in a respective slot which is formed in the respective side wall, of which slot 98 which receives pivot end 96 is shown in Figure 8. Vertically above each slot there is provided a tapered recess 100 which is defined by three inclined surfaces 101, 102 and 103.

Situated between the rearmost portions 43 and 44 of the side walls 35 and 36 the body 5 comprises a base portion 103. Perpendicular to the base portion 103 there is provided a wall 110.

As seen best in Figure 1, that section of the pivot end which lies between the pivot ends 95 and 96 comprises a rounded outer surface portion 105. The rounded surface portion 105 leads to an edge protrusion 106 which is contiguous with a substantially flat surface portion 107.

The operation of the catheter clamp 1 will now be described. The clamp is assembled by initially aligning the pivot ends 95 and 96 over the respective recesses 100. The pivot ends are then urged into the recesses so as to slightly compress the pivot ends and so momentarily deflecting the wall portions 43 and 44 and guide the same into their respective slots.

The cap 3 is then caused to adopt an open condition in which said cap is substantially perpendicular to the body 5. In such a condition the flat surface portion 107 rests on the base portion 103. The wall 110 acts as a stop means to prevent the cap from being pivoted back any further than the perpendicular position.

The catheter is fed through the underside of the body 5 via the part-circular wall 11 and the part conical surface 20 until the catheter clamp can be positioned above the insertion site of the catheter (not shown). The part conical surface 20 facilitates the initial clamp positioning step.

An adhesive on the underside of the foam pad 7 is exposed by peeling away a release paper, and the adhesive contacting the patient's skin to hold the clamp in position.

The appropriate portion of the catheter is then urged into the channel portions 14 and 15 which are dimensioned so as to provide a close fitting pathway for the catheter. The catheter is thus located as shown in Figure 1.

- 5 The apertures 25 allow the position of the insertion site to be viewed and so ensure correct location of the clamp relative to the insertion site.

The cap 3 is then pivoted generally downwardly so that the clips 59 and 60 initially engage with the tapered recesses 55 and 56 respectively. In order to pivot the cap 3 from the open condition to the closed condition, the edge protrusion 106 engages with the base portion 103 so as to deflect said base portion and thus a force needs to be overcome in order for the cap to adopt the closed condition. Further depression of the cap 3 causes the depending portions 112 and 113 to be compressed and subsequently snap into position against the flanged portions 61 and 62 of the side wall portions 38 and 39. The cap 3 is now in the clamping condition shown in Figure 1.

In the clamping condition a portion 115 of the underside of the cap 3 engages with that portion of the catheter 2 which is located by the channel portions 14 and 15 so as to urge the catheter into said channel portions. As is evident from Figure 1 the longitudinal cross-sectional profile of surface 115 is substantially the same as that of the channel portions 14 and 15. The ribs 16 act so as to substantially restrict movement of the catheter in a direction which is substantially parallel to the longitudinal axis of the channel portions.

- 25 In the clamping condition the interface surface 91 of the cap 3 bears against the interface surface 26 of the body 5 so as to form a barrier which substantially prevents an ingress of bacteria.

Such a barrier is achieved by forcing the surfaces 26 and 91 together sufficiently by the action of strain energy in the limbs 81 and 82. This strain energy is brought about on one hand by the co-operation between pivot ends 95 and 96 bearing against the rear side walls 44 and 45 and on
5 the other hand by the co-operation between clips 59 and 60 bearing against the surfaces 61 and 62.

The recess 92 of the abutment 90 and the channel portion 15 form a tight grip around the respective part of the catheter by way of a tight-fitting hole and similarly prevent an ingress of bacteria.

- 10 The hinged portions 52 and 53 allow for the clamp 1 to be sited on an irregular surface so that those portions can be configured to more closely follow the contours of a patient's body.

Although in the above described and illustrated embodiment the cap 3 clamps that portion of the catheter which is located by the inclined
15 channel 14, in a alternative embodiment of the invention the cap 3 may comprise a surface portion which in addition or alternatively that clamping action acts to clamp that portion of the catheter which is located by the curved edge 12.

- 20 Figure 9 shows an alternative embodiment which is substantially identical to the clamp 1 in which a first location portion is provided by an inclined surface 120. This embodiment advantageously allows the clamp to be used with catheters which exit from the skin at an acute angle.

CLAIMS

1. A catheter clamp comprising a body portion (5) and a clamping means (3), the body portion comprising catheter location means, the catheter location means comprising a first location portion (11) which
5 receives a catheter (2) which issues from a patient's skin, a second location portion (12) which causes the catheter to be bent through an arc and a third location portion (13) which guides the catheter to an exit of the clamp, the third location portion comprising side walls which flank the catheter so as to form a close-fitting pathway, the arrangement of the
10 clamp being such that in use the clamping means is manually operable and can be caused to adopt a clamping condition in which the clamping portion clamps at least one of that portion of the catheter which is located by the third location portion and that portion of the catheter which is located by the second location portion.
- 15 2. A catheter clamp as claimed in claim 1, in which the second location portion (12) comprises side walls which flank the catheter so as to form a close-fitting pathway.
3. A catheter clamp as claimed in claim 1 or claim 2, in which the clamping means (3) comprises a hinge (95, 96) and an arm (81, 82, 84),
20 the hinge pivotally mounting the arm to the body portion (5).
4. A catheter clamp as claimed in claim 3, in which the arm comprises arm retention means adapted to hold the arm in a clamping condition, said arm retention means comprising co-operating formations (59, 60, 61, 62) provided on said arm and on the body portion.

5. A catheter clamp as claimed in claim 4, in which the hinge (95, 96) and the arm retention means (59, 60, 61, 62) are provided substantially diametrically of the arm (3).
6. A catheter clamp as claimed in claim 1 in which the clamping means
5 comprises a clamping surface (115) which has a longitudinal cross-sectional profile which is substantially the same as that of the third location portion (13).
7. A catheter clamp as claimed in claim 1, in which in the clamping
10 condition the clamping means (3) at least partially encloses a region in which the insertion site is located.
8. A catheter clamp as claimed in claim 1, in which in the clamping
condition respective complementary interface surfaces (26, 91) of the
clamping means (3) and the body (5) bear against each other to form a
barrier to the insertion site which substantially prevents an ingress of
15 bacteria.
9. A catheter clamp as claimed in claim 8, in which the clamping
means (3) comprises a formation (92) in the respective interface surface
which in part allows the catheter to exit the catheter clamp.
10. A catheter clamp as claimed in claim 9, in which the third location
20 portion (13) comprises catheter gripping means (16) which at least substantially restricts movement of the catheter in a direction which is substantially parallel to a longitudinal axis of the third location portion.
11. A catheter clamp as claimed in claim 10, in which the gripping
means comprises a rib (16) which extends substantially perpendicular to
25 the longitudinal axis of the third location portion (13).

12. A catheter clamp as claimed in claim 11, in which a plurality of ribs (16) is provided.

13. A catheter clamp as claimed in claim 1, in which the body portion (5) comprises viewing means (25) which allows a region proximal 5— to the insertion site to be viewed.

14. A catheter clamp as claimed in claim 13, in which the viewing means (25) is provided by at least one aperture.

1/8





Fig. 1

3/8

**Fig. 3**

4/8




Fig. 4




Fig. 5

5/8




Fig. 6




Fig. 7




Fig. 8

6/8




Fig. 9

7/8




Fig. 10

8/8




Fig. 11

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/00539

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61M25/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	US 5 690 616 A (MOGG ALAN DAVID) 25 November 1997 (1997-11-25) column 1, line 34 -column 2, line 13; figures 1-7 column 3, line 19 -column 4, line 20	1-7 8-14
X A	DE 197 741 C (BRAUN MELSUNGEN AG ;MEDI GLOBE GIP MEDIZIN TECHNIK (DE)) 5 November 1998 (1998-11-05) column 1, line 50 -column 2, line 24; figures 1-5	1-7 8-14
X A	GB 2 288 538 A (MOGG ALAN DAVID) 25 October 1995 (1995-10-25) page 1, paragraph 5 -page 4, paragraph 4; figures 1-3	1-7 8-14
	-/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the international search

9 May 2003

Date of mailing of the international search report

04/06/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Cuiper, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/00539

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 659 329 A (ANNIS LARRY D) 21 April 1987 (1987-04-21) figures 1,2	1-14
A	US 4 533 349 A (BARK JEFFREY E) 6 August 1985 (1985-08-06) figures 1-4	1-14
A	EP 0 327 299 A (BARD LTD) 9 August 1989 (1989-08-09) claim 1; figures 1-5	1-14
A	GB 2 147 811 A (BRISTOL MYERS CO) 22 May 1985 (1985-05-22) figure 1	1-14

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/GB 03/00539

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5690616	A	25-11-1997	NONE
DE 19749741	C	05-11-1998	DE 19749741 C1 05-11-1998 WO 9924103 A1 20-05-1999 EP 1030707 A1 30-08-2000 JP 2001522664 T 20-11-2001
GB 2288538	A	25-10-1995	GB 2288542 A , B 25-10-1995
US 4659329	A	21-04-1987	NONE
US 4533349	A	06-08-1985	NONE
EP 0327299	A	09-08-1989	AT 80560 T 15-10-1992 CA 1318824 A1 08-06-1993 DE 68902839 D1 22-10-1992 DE 68902839 T2 01-04-1993 EP 0327299 A2 09-08-1989 ES 2035544 T3 16-04-1993 IE 63644 B1 31-05-1995 NO 890423 A , B, 07-08-1989
GB 2147811	A	22-05-1985	AU 561872 B2 21-05-1987 AU 3413484 A 18-04-1985 DE 3432937 A1 02-05-1985 FR 2552995 A1 12-04-1985 IT 1178032 B 03-09-1987 JP 60100973 A 04-06-1985 US 4645492 A 24-02-1987